

Multi-Position Air Handler Models



"BLN" / "BLNT" / "SL" / "SLT"
Multi-Position Air Handlers
Patent Product

Features:

- Multi-Position Up-Flow and Horizontal (Units comes Up-Flow, Horizontal Left or Horizontal Right) (Field convertible to the opposite Horizontal direction)
- Polymer drain pan
- Attractive, powder painted exterior
- Fully insulated cabinet
- 208/ 230 VAC operation
- Multi-Speed Direct Drive Blower
- SL* air flow from 600 to 1200 CFM
- SLT* air flow from 800 to 1600 CFM
- BLN* air flow from 1200 to 2000 CFM
- BLNT* air flow from 1600 to 2000 CFM

Optional Features:

- Factory installed Thermal Expansion Valve
- Optional factory installed Electric Heat
3, 5, 6, 8, 10, 15, or 20 kW
- Electrical Disconnect is standard with 15 and 20 kW heaters
- Slide in Long Life Aluminum or Copper DX Coils available
- Field installed Heat kits available from 3 kW - 20 kW
- ECM X-13 Motor

Multi-Position Air Handler Models:

A/C - BLN BLNT BLT
 SL *SLT

Hydronic - *BLNCW *BLNW
 *SLCW *SLW